

SPECIFICATIONS	BOSS																								
MODELS	2552KAJ8-SR1205	2552KAT8-SR1205	2652KALJ8-SR1205	2652KALT8-SR1205	2852KOJ8-SR1205	2852KOT8-SR1205	2660KALJ8-SR1205	2660KALT8-SR1205	2760KOJ8-SR2105	2760KOT8-SR1205	2860KOJ8-SR1205	2860KOT8-SR1205	3160KAJ8-SR1205	3160KAT8-SR1205	3760KSJ8-SR1205	3760KAT8-SR1205	2672KALJ8-SR1205	2672KALT8-SR1205	2872KOT8-SR1205	3172KAJ8-SR1205	3172KAT8-SR1205	3772KAJ8-SR1205	3772KAT8-SR1205		
FEATURES																									
ENGINE	KAWASAKI		KAWASAKI LIQUID COOL		KOHLER EFI		KAWASAKI LIQUID COOL		KOHLER		KOHLER EFI		KAWASAKI			KAWASAKI LIQUID COOL		KOHLER EFI		KAWASAKI					
HORSEPOWER	25		26		28		26		27		28		31			37		26		28		31		37	
CYLINDERS	TWIN																								
OIL CAPACITY	2 qt w/ filter		2.1 qt w/ filter		2 qt w/ filter		2.1 qt w/ filter		2 qt w/ filter						1.8 qt w/filter		2.1 qt w/ filter		2 qt w/ filter				1.8 qt w/filter		
HYDROSTATIC TRANSMISSION	HYDROGEAR PUMPS AND WHEEL MOTORS																								
STEERING CONTROL	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	
FUEL CAPACITY	11 GALLONS																								
TIRES,REAR	23X9.5												13X650-6						24X12.00						
TIRES,FRONT																									
TURNING RADIUS	ZERO TURN																								
GROUND SPEED,FORWARD	11MPH(INFINITELY VARIABLE)																								
REVERSE	3-1/2MPH INFINITELY VARIABLE)																								
LENGTH	86-1/2"																								
HEIGHT	32"(SEAT CUSHION) 49"(TOP OF SEAT BACK)																								
WIDTH, TRACTOR(OUTSIDE REAR TIRES)	48"												55-1/4"												
DECK, WIDTH WITH CHUTE	61"												69-1/2"						81-1/2"						
CUTTING WIDTH	52"												60"						72"						
BLADE LENGTH (3EA)	18-3/8"												21"						25"						
SINDLE ASSY	CAST IRON HOUSING W/ 1-1/8 SHAFT GREASABLE																								
CONSTRUCTION	FULL COMPLEMENT FRONT/ REAR BAFFLES REINFORCED BULL NOSE/ MULTI LAYER LAMINATED DECK SHELL, FABRICATED, WELDED , 3 BLADES																								
	ANTI SCALPING ROLLERS																								
	STAND UP DECK																								
CUTTING HEIGHT	1-1/2"TO 5"																								
BLADE CLUTCH	STANDARD																								
BLADE TIP SPEED	ALL DECKS APPROXIMATE 19000 FT/MIN EXCEPT 38 IN APPROX 17000 FT/MIN																								
WEIGHT	1100												1120						1220						
ELECTRIC START	STANDARD																								
HOUR METER	STANDARD																								
CUP HOLDER	NO, HAS TRAY																								
ARM RESTS	STANDARD																								
HEAD LIGHT KIT	OPTION																								
MULCH KIT	OPTION																								
PIVOTING FRONT END	STANDARD																								