

SPECIFICATIONS

CHARGER

MODELS	2348KOJ8-SR1005	2348KOT8-SR1005	2352KOJ8-SR1005	2352KOT8-SR1005	2552KAJ8-SR1005	2552KAT8-SR1005	2560KAJ8-SR1005	2560KAT8-SR1005	2760KOJ8-SR1005	2760KOT8-SR1005	3060KOJ8-SR1005	3060KOT8-SR1005
FEATURES												
ENGINE	KOHLER			KOHLER COMMAND			KAWASAKI			KOHLER COMMAND PRO		
HORSEPOWER	23				25				27		30	
CYLINDERS	TWIN											
OIL CAPACITY	2 qt w/ filter											
HYDROSTATIC TRANSMISSION	HYDROGEAR PUMPS PARKER-ROSS WHEEL MOTORS											
STEERING CONTROL	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK	JOYSTICK	TWIN STICK
FUEL CAPACITY	8 GALLONS											
TIRES,REAR	23X9.50-12		24X12-12		23X9.50-12		24X12-12					
TIRES,FRONT	13X6.50-6											
TURNING RADIUS	ZERO TURN											
GROUND SPEED,FORWARD	10MPH(INFINTELY VARIABLE)											
REVERSE	5MPH(INFINITELY VARIABLE)											
LENGTH	82-1/2"											
HEIGHT	28"(SEAT CUSHION) 41"(TOP OF SEAT)											
WIDTH, TRACTOR (OUTSIDE REAR TIRES)	48"		51-1/4"		48"		51-1/4"					
DECK WIDTH WITH CHUTE	58"		62"		58"		62"		70"			
CUTTING WIDTH	48"	48"	52"	52"	48"	48"	52"	52"	60"	60"	60"	60"
BLADE LENGTH (3EA)	17"	17"	18-3/8"	18-3/8"	17"	17"	18-3/8"	18-3/8"	21"	21"	21"	21"
SINDLE ASSY	CAST IRON HOUSING W/ I-1/8 SHAFT GREASABLE											
CONSTRUCTION	FULL COMPLEMENT FRONT/ REAR BAFFLES REINFORCED BULL NOSE/ MULTI LAYER LAMINATED DECK SHELL, FABRICATED, WELDED , 3 BLADES											
	ANTI SCALPING ROLLERS											
	STAND UP DECK											
CUTTING HEIGHT	1 1/2" TO 5 1/4" INCREMENTS											
BLADE CLUTCH	ELECTRIC											
BLADE TIP SPEED	ALL DECKS APPROXIMATE 19000 FT/MIN EXCEPT 38 IN APPROX 17000 FT/MIN											
WEIGHT	1100#											
ELECTRIC START	STANDARD											
HOUR METER	STANDARD											
CUP HOLDER	STANDARD											
ARM RESTS	STANDARD											
HEAD LIGHT KIT	OPTION											
MULCH KIT	OPTION											
PIVOTING FRONT END	STANDARD											