

## Charger specifications

Feature	Model			
	2352KOJ-SR1010	2352KOT-SR1010	2552KAJ-SR1010	2552KAT-SR1010
Engine	Kohler Command Pro		Kawasaki V-Twin	
Horsepower	23 hp		25 hp	
Cylinders	Twin			
Oil Capacity	2 qt w/ filter			
Transmission	Dual HydroGear 10 cc pumps and Parker Ross wheel motors			
Hydro Oil Cooler	Standard			
Steering Control	Joystick	Dual Lever	Joystick	Dual Lever
Fuel Capacity	8 gal			
Tires, Rear	23 x 9.50 - 12			
Tires, Front	13 x 6.50 - 6			
Turning Radius	Zero-Turn			
Ground Speed Forward	10 mph			
Reverse	5 mph			
Length	82.5"			
Height: top of seat back	43"			
Width, Tractor (outside rear tires)	49"			
Deck, Width w/chute	62"			
Cutting Width	52"			
Blade Length (each of 3)	18 <sup>3</sup> / <sub>8</sub> "			
Spindle Assembly	Cast iron housing and 1.125" shaft (Spindle Pulleys also machined cast iron)			
Deck Construction	Full complement front/rear baffles, reinforced bullnose front; fabricated, multi-layered laminated deck shell, 3 blades, anti-scalp rollers, stand-up deck			
Cutting Height	1.5" to 5"			
Blade Clutch	Electric			
Blade Tip Speed	19,000 fpm			
Weight	1100 lbs			
Electric Start	Standard			
Hour Meter	Standard			
Cup Holder	Standard			
Arm Rests	Standard			
Head Light Kit	Option			
Mulch Kit	Option			
Pivoting Front End	Standard			

Due to continuous product improvement, all specifications are subject to change without notice.

## Charger specifications

Feature	Model			
	2560KAJ-SR1010	2560KAT-SR1010	2760KOJ-SR1010	2760KOT-SR1010
Engine	Kawasaki V-Twin		Kohler Command Pro	
Horsepower	25 hp		27 hp	
Cylinders	Twin			
Oil Capacity	2 qt w/ filter			
Transmission	Dual HydroGear 10 cc pumps and Parker Ross wheel motors			
Hydro Oil Cooler	Standard			
Steering Control	Joystick	Dual Lever	Joystick	Dual Lever
Fuel Capacity	8 gal			
Tires, Rear	24 x 12.00 - 12			
Tires, Front	13 x 6.50 - 6			
Turning Radius	Zero-Turn			
Ground Speed Forward	10 mph			
Reverse	5 mph			
Length	82.5"			
Height: top of seat back	43"			
Width, Tractor (outside rear tires)	51.25"			
Deck, Width w/chute	70"			
Cutting Width	60"			
Blade Length (each of 3)	21"			
Spindle Assembly	Cast iron housing and 1.125" shaft (Spindle Pulleys also machined cast iron)			
Deck Construction	Full complement front/rear baffles, reinforced bullnose front; fabricated, multi-layered laminated deck shell, 3 blades, anti-scalp rollers, stand-up deck			
Cutting Height	1.5" to 5"			
Blade Clutch	Electric			
Blade Tip Speed	19,000 fpm			
Weight	1100 lbs			
Electric Start	Standard			
Hour Meter	Standard			
Cup Holder	Standard			
Arm Rests	Standard			
Head Light Kit	Option			
Mulch Kit	Option			
Pivoting Front End	Standard			
Due to continuous product improvement, all specifications are subject to change without notice.				